

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 September 2005 (15.09.2005)

PCT

(10) International Publication Number
WO 2005/085014 A1

(51) International Patent Classification⁷: **B60R 21/13,**
21/34

(74) Agent: ALBIHNS STOCKHOLM AB; P O Box 5581,
S-114 85 Stockholm (SE).

(21) International Application Number:
PCT/SE2005/000260

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(22) International Filing Date: 24 February 2005 (24.02.2005)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:
0400550-0 5 March 2004 (05.03.2004) SE

(71) Applicant (for all designated States except US): SAAB
AUTOMOBILE AB [SE/SE]; S-461 80 Trollhättan (SE).

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,


(72) Inventor; and

(75) Inventor/Applicant (for US only): KARLSSON, Mikael
[SE/SE]; Bäckängen Tun, S-467 94 Grästorp (SE).

[Continued on next page]

(54) Title: LIFTING DEVICE

(57) Abstract: The present invention relates to a lifting device (1) to be mounted in a motor vehicle and intended, in case the vehicle is involved in an accident, to be activated by putting a lifting element (5) being spring-tensioned in the lifting device in motion, wherein the lifting device comprises a locking device (7) intended to cooperate with the lifting element (5) for locking it in a spring-tensioned position, and a release mechanism (9) intended to release the locked lifting element (5) so it can be put in motion under the influence of the spring tension. The invention is characterised in that the release mechanism (9) comprises a striking element (37) intended to release the locked lifting element (5) by means of striking-pin action.



WO 2005/085014 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report